

Moffitt Primus Elite
SAE 0W-20, 5W-20, 5W-30 & 10W-30
Full Synthetic Motor Oil, API SP, ILSAC GF-6A

Product Description

Moffitt Primus Elite SAE 0W-20, 5W-20, 5W-30, and 10W-30 are premium full synthetic motor oils manufactured for use in modern gasoline engines which require ILSAC GF-6A, API SP, API SN Plus, or API SN performance.

These oils are formulated with synthetic base oils and a premium performance additive package which is specially formulated to protect high compression gasoline direct injection engines delivering superior oxidative stability, deposit control, low speed pre-ignition mitigation and timing chain wear protection.

Typical Properties*

SAE J300 Viscosity Grade	0W-20	5W-20	5W-30	10W-30
Appearance, Visual	Amber, Transparent, Liquid			
Viscosity @ 40°C, cSt, ASTM D445	44.55	47.75	61.25	68.75
Viscosity @ 100°C, cSt, ASTM D445	8.3	8.3	10.8	10.9
Viscosity Index, ASTM D2270	165	150	170	150
CCS Apparent Viscosity, cP, ASTM D5293	5,400@-35°C	4,800@-30°C	5,200@-30°C	4,900@-25°C
MRV Apparent Viscosity, cP, ASTM D4684	22,000@-40°C	15,000@-35°C	18,000@-35°C	9,000@-30°C
Flash Point, °C, ASTM D92	210	215	215	218
Pour Point, °C, ASTM D97	-47	-44	-42	-40

**The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

Exceeds Performance Requirements

API SP with Resource Conserving, API SN Plus, API SN
 ILSAC GF-6A, GF-5
 GM dexos1™ Gen 2
 Chrysler MS6395
 Ford WSS-M2C947-B1 (0W-20); Ford WSS-M2C945-B1 (5W-20); Ford WSS-M2C946-B1 (5W-30)

Product Code

SAE 0W-20 – SPE002; **SAE 5W-20** – SPE003; **SAE 5W-30** – SPE004; **SAE 10W-30** – SPE005

