

***Moffitt Primus Elite Euro***  
SAE 5W-40; Full Synthetic Motor Oil  
ACEA A3/B4-16, API SN

**Product Description**

**Moffitt Primus Elite Euro SAE 5W-40 Full Synthetic Motor Oil ACEA A3/B4-16, API SN** is formulated with synthetic base oils and a premium additive package. This oil is designed for use in carbureted, fuel injected, turbocharged and supercharged gasoline engines. This oil exceeds the performance requirements of API SN and ACEA A3/B4.

**Typical Properties\***

<b><i>SAE J300 Viscosity Grade</i></b>	<b><i>5W-40</i></b>
Appearance, Visual	Amber, Transparent, Liquid
Viscosity @ 40°C, cSt, ASTM D445	80.0
Viscosity @ 100°C, cSt, ASTM D445	13.5
Viscosity Index, ASTM D2270	172
CCS Apparent Viscosity, cP, ASTM D5293	5,600@-30°C
MRV Apparent Viscosity, cP, ASTM D4684	23,000@-35°C
Flash Point, °C, ASTM D92	210
Pour Point, °C, ASTM D97	-42
Total Base Number, mgKOH/g, ASTM D2896	10.5

*\*The values shown are typical of current production. Some are controlled in the manufacturing process, while others are not. All of them may vary within tolerable ranges.*

**Exceeds Performance Requirements**

ACEA A3/B3-16, A3/B4-16  
API SN/CF  
Porsche A40  
MB 226.5 / 229.3 / 229.5  
BMW LL-01  
VW 502.00, 505.00  
Renault RN0700 / RN0710

**Product Code**

SPE009

